VENTSHIELD | Air Filter with Dustshield **VF Shielding**

Our VF Shielding combines the benefits of an attenuation vent panel with the properties of a dust filter in a single frame, unlike VB Shielding which utilises separate units fixed together in-situ.

Standard frame styles are AF1, AF2, AF3, AF4, AF6, AF7 and AF8 and they incorporate a triple layer of woven and corrugated aluminium mesh. Each layer has a slightly different degree of corrugation and so provides separation and increased airflow potential. To enable it to perform its dual function the VF filter material is relatively dense and so requires an assisted airflow to operate correctly. A 'kick plate' is built into the unit to protect the filter from damage.

Aluminium mesh dust filters are mounted in the same manner as the VH Shielding and are used in industrial or military environments where a 'heavy duty' attenuating dust filter is required and a lighter weight de-membraned polyurethane VB Shielding is not suitable. They are not designed for pure convection and need a driven airflow. They may be solvent cleaned after removal but particular attention should be paid to the replacement of gaskets which could be affected by compression-set or hydrocarbon/solvent contamination.

Specifications:

Applications:

Woven Aluminium Screen

AMS-4182

Performance: Typical dB


(based on a 250mm ² test section)									
FREQUENCY	FIELD	ATTENUATION							
10KHz	Н	42							
100KHz	Н	53							
1MHz	Н	61							
1MHz	E	92							
10MHz	E	81							
100MHz	Е	60							
1GHz	Р	52							
10GHz	Р	43							

Tolerances:

Overall dimensions +0.8mm Fixing holes/fasteners

±0.5mm with jigs ±0.2mm

VF AF2



How to order:

Specify: Series - Frame Style - Vent Media - Overall Size -Number of Fixings - Fixing Type/Size

Where possible please provide a detailed drawing.

VF-AF1-08-2260-4330-12-T/H (4.8) specifies a corrugated three layer aluminium woven mesh dust-filter in an AF1 style frame with 12 through holes of 4.8 mm diameter. The hole positions would be agreed with the customer prior to manufacture or as shown on the customer drawing.



W: www.p-p-t.co.uk E: info@p-p-t.co.uk

TECHNOLOGY 2
P & P Technology Ltd
Unit 5 Cherry Tree
Wethersfield Road
Halstead, Essex CO9 3LZ

	SERIES	FRAME STYLE	VENT MEDIA	OVERALL SIZE	FIXINGS (NO.)	FIXING TYPE
	VF-Dust Filter	AF1	08=Triple mesh	XXXX-XXXX	XX	C/T=Captive insert
	Aluminium	AF2				T/H=Through hole
P&P		AF3				
P & P Technology Ltd Unit 5 Cherry Tree Wethersfield Road Halstead, Essex CO9 3LZ		AF4				
		AF6				
		AF7				
	Z	AF8				
T: +44 (0) 1376 550 525						