

AC-DC modules - OFF BOARD (HOUSING) - 320, 350 and 450 watt

SCP = Short Circuit Protection

Power	Series	Case Size	Input Range	Input Voltage (VAC/VDC)	Output Voltage (VDC)	Isolation	Regulation	SCP	n max.	Operating Temp.	Certification	PFC
320	320ACPE_C4	215.0 x 115.0 x 30.0mm	wide	85-264VAC; 47-63Hz; 120-373VDC	5; 12; 15; 14; 48	4kVAC	▪	▪	87,5%	-30°C - +70°C	UL62368	
320	320ACPW_C4	215.0 x 115.0 x 30.0mm	wide	85-305VAC; 47-63Hz; 100-430VDC	4; 5; 12; 15; 24; 27; 48	4kVAC	▪	▪	87,5%	-30°C - +70°C	UL62368	
350	320ACPE_C4	127.0 x 76.2 x 25.4mm	wide	90-264VAC; 47-63Hz 127-373VDC	12; 15; 24; 27; 36; 48	4kVAC	▪	▪	94%	-40°C - +70°C	UL60601	
450	450ACPE_C4	215.0 x 115.0 x 30.0mm	wide	176-264VAC; 47-63Hz; 240-373VDC	12; 15; 24; 48	4kVAC	▪	▪	88%	-30°C - +70°C	UL62368	



AC-DC modules - OFF BOARD (OPEN FRAME) - 3, 5, 10 and 15 watt

3	3ACFO_3	42 x 16 x 17mm	wide	85-264VAC; 47-63Hz 120-370VDC	3.3; 5; 9; 12; 15; 24	3kVAC	▪	▪	79%	-25°C - +70°C		
5	5ACFO_3	42 x 16 x 17mm	wide	165-264VAC; 47-63Hz; 230-370VDC	3.3; 5; 9; 12; 15; 24	3kVAC	▪	▪	79%	-25°C - +70°C		
10	10ACO_4	80 x 40 x 30mm	wide	30 - 280VAC; 30-400VDC	5, 12, 15	4kVAC	▪	▪	77%	-25°C ~ 70°C	UL62368	
10	10ACOW_3	60 x 42 x 16.3mm	wide	85-305VAC; 47-63Hz; 100-430VDC	3.3; 5; 9; 12; 15; 24	3kVAC	▪	▪	81%	-25°C - +70°C	UL62368	
15	15ACO_3	63.5 x 45.7 x 19.0mm	wide	85-264VAC; 47-63Hz; 120-370VDC	3.3; 5; 9; 12; 15	3kVAC	▪	▪	81%	-25°C - +70°C		
15	15ACOW_4	87.5 x 50.0 x 22.0mm	wide	85-305VAC; 47-63Hz 100-430VDC	3.3; 5; 12; 15; 24	4kVAC	▪	▪	85%	-25°C - +70°C		



AC-DC modules - OFF BOARD (OPEN FRAME) - 3, 5, 10, 15, 30, 45, 65, 120 and 180 watt

SCP = Short Circuit Protection

Power	Series	Case Size	Input Range	Input Voltage (VAC/VDC)	Output Voltage (VDC)	Isolation	Regulation	SCP	n max.	Operating Temp.	Certification	PFC
30	30ACO_3	76.2 x 44.45 x 27.0mm	wide	85-264VAC; 47-63Hz 120-370VDC	3.3; 5; 9; 12; 15; 24; 48	3kVAC	▪	▪	90%	-30°C - +70°C	UL62368	
45	45ACO_3	76.2 x 50.8 x 30.0mm	wide	85-264VAC; 47-63Hz 100-370VDC	3.3; 5; 9; 12; 15; 24; 48	3kVAC	▪	▪	87%	-25°C - +70°C	UL62368	
65	65ACMOP	76.2 x 50.8 x 28.7mm	wide	90-264VAC; 47-63Hz	5, 12, 15, 19, 20, 24, 28,48, 56	4kVAC	▪	▪	87%	-20°C - +70°C	UL60601	
65	65ACO_3	76.2 x 44.8 x 30.0mm	wide	85-264VAC; 47-63Hz; 120-373VDC	5; 9; 12; 15; 24; 48	3kVAC	▪	▪	87%	-25°C - +70°C	UL62368	
120	120ACMOP_C4	76.2 x 50.8 x 3.0mm	wide	90-264VAC; 47-63Hz; 127-370VDC	12; 15; 19; 24; 27; 36; 48; 54	4kVAC	▪	▪	95%	-40°C - +85°C	UL62368	
180	180ACMOP	127 x 76.2 x 30 mm	wide	90-264VAC; 47-63Hz;	12, 15, 19, 24, 28, 48	4kVAC	▪	▪	87%	-0°C - +60°C	UL60601	
225	225ACMOP_C4	101 x 50.8 x 25.4mm	wide	85-264VAC; 47-63Hz; 120-370VDC	12; 15; 24; 27; 36; 48	4kVAC	▪	▪	94%	-40°C - +70°C	UL60601 UL62368	
280	280ACMOP	127 x 76.2 x 30mm	wide	85-305VAC; 47-63Hz 100-430VDC	12; 24; 28; 36; 48; 54	4kVAC	▪	▪	91%	-20°C - +70°C	UL60601	
360	360ACMOP	152.4 x 101.6 x 30mm	wide	90-264VAC; 47-63Hz;	12, 24, 28, 48, 54	4kVAC	▪	▪	90%	0°C - +70°C	UL60601	
450	450ACMOP_C4	127.0 x 76.2 x 38.5mm	wide	90-264VAC; 47-63Hz; 127-370VDC	12; 15; 24; 27; 36; 48	4kVAC	▪	▪	94%	-40°C - +70°C	UL60601 UL62368	
550	550ACMOP_C4	127.1 x 76.20 x 40.5mm	wide	90-264VAC; 47-63Hz; 240-373VDC	12, 15; 24, 27, 36, 48	4kVAC	▪	▪	94%	-40°C - +70°C	UL62368 UL60601	