

AC-DC modules - OFF BOARD (HOUSING) - 15, 25, 35, 50, 75, 100, 150 and 280 watt

SCP = Short Circuit Protection

Power	Series	Case Size	Input Range	Input Voltage (VAC/VDC)	Output Voltage (VDC)	Isolation	Regulation	SCP	n max.	Operating Temp.	Certification	PFC
15	15ACPW_4	65 x 55 x 25mm	wide	85-305VAC; 47-63Hz 100-430VDC	3.3; 5; 12; 15; 24; 48	4kVAC	▪	▪	83%	-30°C - +70°C	UL62368	
25	25ACPW_4	65 x 55 x 25mm	wide	85-305VAC; 47-63Hz; 100-430VDC	3.3; 5; 12; 15; 24; 48	4kVAC	▪	▪	83%	-30°C - +70°C	UL62368	
35	35ACPE_4	99 x 82 x 26mm	wide	85-264VAC; 47-63Hz; 120-373VDC	5; 12; 15; 24	4kVAC	▪	▪	89%	-30°C - +70°C	UL62368	
35	35ACPW_4	92.5 x 82 x 26mm	wide	85-305VAC; 47-63Hz 100-430VDC	5; 12; 15; 24	4kVAC	▪	▪	87%	-30°C - +70°C	UL62368	
50	50ACPE_4	92.5 x 82 x 30mm	wide	85-264VAC; 47-63Hz; 120-373VDC	5; 12; 15; 24	4kVAC	▪	▪	90%	-30°C - +70°C	UL62368	
50	50ACPW_4	92.5 x 82 x 30mm	wide	85-305VAC; 47-63Hz 100-430VDC	5; 12; 15; 24	4kVAC	▪	▪	87%	-30°C - +70°C	UL62368	
75	75ACPE_4	92.5 x 97 x 30mm	wide	85-264VAC; 47-63Hz; 120-373VDC	5; 12; 15; 24	4kVAC	▪	▪	87%	-30°C - +70°C	UL62368	
75	75ACPW_4	92.5 x 97 x 30mm	wide	85-305VAC; 47-63Hz; 100-430VDC	5; 12; 15; 24	4kVAC	▪	▪	87%	-30°C - +70°C	UL62368	
100	100ACPE_4	122.5 x 97 x 30mm	wide	85-264VAC; 47-63Hz; 120-373VDC	5; 12; 15; 24; 36; 48	4kVAC	▪	▪	87%	-30°C - +70°C	UL62368	
100	100ACPW_4	122.5 x 97 x 30mm	wide	85-305VAC; 47-63Hz; 100-430VDC	5; 12; 15; 24; 36; 48	4kVAC	▪	▪	87%	-30°C - +70°C	UL62368	
150	100ACPE_4	152.45 x 97 x 30mm	wide	85-264VAC; 47-63Hz; 120-370VDC	12; 15; 24; 36; 48	4kVAC	▪	▪	87%	-30°C - +70°C	UL62368	
150	100ACPW_4	152.45 x 97 x 30mm	wide	85-305VAC; 47-63Hz; 100-430VDC	12; 15; 24; 36; 48	4kVAC	▪	▪	87%	-30°C - +70°C	UL62368	
225	225ACPE_4	65 x 55 x 25mm	wide	85-305VAC; 47-63Hz; 100-430VDC	12; 15; 24; 36; 48	4kVAC	▪	▪	94%	-30°C - +70°C	UL62368	
280	280ACMHP	127 x 83.2 x 39.5mm	wide	90-264VAC; 47-63Hz;	12, 24, 28, 36, 48, 54	4kVAC	▪	▪	91%	-20°C - +70°C	UL60601	



AC-DC modules - OFF BOARD (HOUSING) - 320, 350 and 450 watt

SCP = Short Circuit Protection

Power	Series	Case Size	Input Range	Input Voltage (VAC/VDC)	Output Voltage (VDC)	Isolation	Regulation	SCP	n max.	Operating Temp.	Certification	PFC
320	320ACPE_C4	215.0 x 115.0 x 30.0mm	wide	85-264VAC; 47-63Hz; 120-373VDC	5; 12; 15; 14; 48	4kVAC	▪	▪	87,5%	-30°C - +70°C	UL62368	
320	320ACPW_C4	215.0 x 115.0 x 30.0mm	wide	85-305VAC; 47-63Hz; 100-430VDC	4; 5; 12; 15; 24; 27; 48	4kVAC	▪	▪	87,5%	-30°C - +70°C	UL62368	
350	320ACPE_C4	127.0 x 76.2 x 25.4mm	wide	90-264VAC; 47-63Hz 127-373VDC	12; 15; 24; 27; 36; 48	4kVAC	▪	▪	94%	-40°C - +70°C	UL60601	
450	450ACPE_C4	215.0 x 115.0 x 30.0mm	wide	176-264VAC; 47-63Hz; 240-373VDC	12; 15; 24; 48	4kVAC	▪	▪	88%	-30°C - +70°C	UL62368	



AC-DC modules - OFF BOARD (OPEN FRAME) - 3, 5, 10 and 15 watt

3	3ACFO_3	42 x 16 x 17mm	wide	85-264VAC; 47-63Hz 120-370VDC	3.3; 5; 9; 12; 15; 24	3kVAC	▪	▪	79%	-25°C - +70°C		
5	5ACFO_3	42 x 16 x 17mm	wide	165-264VAC; 47-63Hz; 230-370VDC	3.3; 5; 9; 12; 15; 24	3kVAC	▪	▪	79%	-25°C - +70°C		
10	10ACO_4	80 x 40 x 30mm	wide	30 - 280VAC; 30-400VDC	5, 12, 15	4kVAC	▪	▪	77%	-25°C ~ 70°C	UL62368	
10	10ACOW_3	60 x 42 x 16.3mm	wide	85-305VAC; 47-63Hz; 100-430VDC	3.3; 5; 9; 12; 15; 24	3kVAC	▪	▪	81%	-25°C - +70°C	UL62368	
15	15ACO_3	63.5 x 45.7 x 19.0mm	wide	85-264VAC; 47-63Hz; 120-370VDC	3.3; 5; 9; 12; 15	3kVAC	▪	▪	81%	-25°C - +70°C		
15	15ACOW_4	87.5 x 50.0 x 22.0mm	wide	85-305VAC; 47-63Hz 100-430VDC	3.3; 5; 12; 15; 24	4kVAC	▪	▪	85%	-25°C - +70°C		

